

**Slimline Window System Standard Heights**

Standard Height sizes are measured from bottom of visible metal to top of visible metal.

No. of Blades	Slimline Window System with 152mm Galleries	Easyscreen Window System with 102mm Galleries
	Standard Height (mm)	Standard Height (mm)
2	345	-
3	485	335
4	625	425
5	765	515
6	905	605
7	1045	695
8	1185	785
9	1325	875
10	1465	965
11	1605	1055
12	1745	1145
13	1885	1235
14	2025	1325
14 Ext	2100	-
15	2165	1415
16	2305	1505
16 Ext	2400	-
17	2445	1595
18	2585	1685
19	2725	1775
20	2865	1865
21	3005	1955
22	-	2045
22 Ext	-	2100
23	-	2135
24	-	2225
25	-	2315
26	-	2405
27	-	2495
28	-	2585
29	-	2675
30	-	2765
31	-	2855
32	-	2945
33	-	3035

**Notes**

- Slimline windows with multiple bays and heights of over 10 and 16 blades respectively for 152mm and 102mm Galleries will require Heavy Duty Mullions.
- Off-standard heights that are not within 5 mm of a standard height have a fixed blade at the top to achieve the specific height.
- Refer to the product performance warranty on possible height restrictions for different blade types and bay widths.
- Standard sizes will save money and improve lead times.
- Maximum width = 4000mm (frames over these dimensions will need to be coupled together on site or at a window fabricator's factory).
- Up to 6 bays (sets of galleries) can be included in a single surround frame.
- Window Systems with Fixed Galleries consist of 152mm clips and blades spaced as far apart as 102mm clips are spaced on normal galleries. Fixed galleries are permanently fixed with the blades at a 45 degree angle.
- Window Systems with Fixed Galleries do not meet water penetration requirements.
- Window Systems with Fixed Galleries are only available in standard heights.