

Altair® Window System Standard Heights

Standard Height sizes are measured from bottom of visible metal to top of visible metal.

No. of Blades	152mm Galleries		
	ios™ Window System	Slimline™ Window System	Easyscreen™ Powerlouvre™ Window System
2	346	345	371
3	486	485	511
4	626	625	651
5	766	765	791
6	906	905	931
7	1046	1045	1071
8	1186	1185	1211
9	1326	1325	1351
10	1466	1465	1491
11	1606	1605	1631
12	1746	1745	1771
13	1886	1885	1911
14	2026	2025	2051
14 Ext	2100	2100	2100
15	2166	2165	2191
16	2306	2305	2331
16 Ext	2400	2400	2400
17	2446	2445	2471
18	2586	2585	2611
19	2726	2725	-
20	2866	2865	-
21	3006	3005	-

No. of Blades	102mm Galleries		
	ios™ Window System	Slimline™ Window System	Easyscreen™ Powerlouvre™ Window System
3	336	335	361
4	426	425	451
5	516	515	541
6	606	605	631
7	696	695	721
8	786	785	811
9	876	875	901
10	966	965	991
11	1056	1055	1081
12	1146	1145	1171
13	1236	1235	1261
14	1326	1325	1351
15	1416	1415	1441
16	1506	1505	1531
17	1596	1595	1621
18	1686	1685	1711
19	1776	1775	-
20	1866	1865	-
21	1956	1955	-
22	2046	2045	-
22 Ext	2100	2100	-
23	2136	2135	-
24	2226	2225	-
25	2316	2315	-
26	2406	2405	-
27	2496	2495	-
28	2586	2585	-
29	2676	2675	-
30	2766	2765	-
31	2856	2855	-
32	2946	2945	-
33	3036	3035	-

Notes

- Slimline windows with multiple bays and heights of over 10 and 16 blades respectively for 152mm and 102mm Galleries will require Heavy Duty Mullions.
- Off-standard heights that are not within 5 mm of a standard height have a fixed blade at the top to achieve the specific height.
- Refer to the product performance warranty on possible height restrictions for different blade types and bay widths.
- Standard sizes will save money and improve lead times.
- Maximum width = 4000mm (frames over these dimensions will need to be coupled together on site or at a window fabricator's factory).
- Up to 6 bays (sets of galleries) can be included in a single surround frame.
- Window Systems with Fixed Galleries consist of 152mm clips and blades spaced as far apart as 102mm clips are spaced on normal galleries. Fixed galleries are permanently fixed with the blades at a 45 degree angle.
- Window Systems with Fixed Galleries do not meet water penetration requirements.
- Window Systems with Fixed Galleries are only available in standard heights.